

3M™ Extreme Sealing Tape 4411 & 4412 Series

Extremely
Fast,
Clean &
Easy



From trailer, bus and rail car roof seams to metal enclosures, a sure winner over traditional sealants

3M™ Extreme Sealing Tape – instant sealing that rolls on fast and looks good

- Sticks on contact to many metals and plastics without drying time, dripping, oozing and clean-up
- No sticky adhesive mess
- Conforms over contours, edges, rivets and screw heads for a water tight seal
- No caulking guns to buy, clean and store and no empty cartridges for disposal
- Paintable to colour-blend with the adjoining surfaces
- Neat and precise looking to improve aesthetics

Over time even more extreme advantages become obvious

- Holds securely through sun, rain, snow, temperature extremes and abrasion
- Stays flexible to compensate for vibration and thermal expansion/contraction
- No cracking and crumbling

- Trailer and RV roofs
- Metal enclosures
- Awnings
- Trailer home roofs
- Metal buildings
- Vent stacks and vent windows
- Gutters and downspouts
- Skylights
- Outdoor sign/display
- Leak patching and temporary repairs
- Almost anywhere sealants are used

5

3M


3M™ Extreme Sealing Tape – rolls on fast, seals instantly and stays tight




STEP 1
Simply clean with a solution of 50:50 water and isopropyl alcohol and wipe dry.



STEP 2
Sticks on contact exactly where you roll it on. No drips and oozing. No waiting.



STEP 3
Roll down with a soft roller to conform over contours, seam edges, rivets or screw heads.



STEP 4
Peel off the protective release liner.

The winner over liquid sealants

3M™ Extreme Sealing Tapes seal seams with roll-on speed for increased productivity and permanent strength for long term confidence with assured and consistent sealing results.

The winner over other tapes

With high shear and peel strengths, 3M™ Extreme Sealing Tapes seal with confidence through heat, cold and weather without cracking or edge lifting and with proven outdoor durability.



Product Information

Product/Colour	Comments	Backing/Adhesive	Tape Thickness (mm)	Tensile Strength (N/cm)	90° Peel Strength (N/cm)				Widths (mm)
					Aluminum	Steel	PVC	ABS	
4411G	Colour matched to metal.	Ionomer film/ Pressure sensitive acrylic	1.0	220	26.7	27.3	25.8	27.1	25, 50, 75
4411N	Low profile or economical applications.				25.6	26.4	27.2	28.1	
4412G	Colour matched to metal.		2.0	110	30.8	30.7	32.1	32.2	
4412N	Most robust sealing performance.				31.7	31.5	33.5	32.3	19, 25, 50, 75, 100

N=Neutral/Translucent G=Grey **Note:** This technical information and data should be considered representative or typical only and should not be used for specification purposes.

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If the 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

DISTRIBUTED BY:



Industrial Tapes and Adhesive Division
3M Canada Company

Please recycle. Printed in Canada.
3M is a trademark of 3M. Used under license in Canada.
© 2012, 3M, All rights reserved.
1202-00471 E BA-12-16799



A.E. BLAKE SALES
LES VENTES A.E. BLAKE

For more information please contact us:
In Montreal at 1-800-879-5748
In Toronto at 1-888-664-2643
www.aeblake.ca